

Camera Fisheye Dome IP resolution 6 Megapixel built-in IR LED



Model : ZN8-F7NTFN10L

Specification

Model	ZN8-F7NTFN10L
Image sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	3072*2048@15fps
White Balance	Auto
Shutter Speed	1/5 – 1/20000
Day/Night	TRUE Day/Night
IR LED	6 pcs / 10 m. (Smart IR)
Min. Illumination	Color 0.01Lux(AGC ON);IR ON 0 Lux
WDR	Digital WDR
De-warping	Yes
Lens	1.6mm
Max. Aperture	F2.0
F.O.V	360 degrees
Audio In/Out	1ch Audio In,1ch Audio Out
Network	1 Ethernet (10/100 Base-T) RJ-45 Connector
Frame rate	3072x2048 @15fps 1920x1920 / 1440x1440 / 1920x1080 @ 25fps

Image Compression	H.264 High/Main/Baseline Profile, MJPEG
Protocol	IPV4, IPV6, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, PPOE, Unicast and Multicast supported
Streaming	Stream 1 : 3072x2048 : 1920x1920 : 1440x1440 : 1920x1080 Stream 2 : 1280x1280 : 720x720 : D1
Web Browser	Yes
Security	User security authentication, Reset, Hardware WatchDog
SDK	Yes
VMD	Yes
Alarm Trigger	Network disconnect, Disk alarm, I/O alarm
Alarm Event	Message display, I/O output, Email snapshot
External I/O Terminal	1ch Alarm I/O
Power Consumption	PoE 12VDC, 24VAC
microSD Card	Max 64GB
Operating Temperature	-20°C~+60°C/0% - 90% RH
Weight	700g
Dimensions	φ 160*46.8
IP Class	IP66
Certifications	FCC / CE