

Camera 2MP, Outdoor WDR/TDN PTZ IP 30x



Model: ZN-P4DT54

Specification

Model:	ZN-P4DT54
Image Sensor	1/2.8" Sony Exmor CMOS
Max. Resolution	1920 x 1080 30fps
Shutter Speed	1/25(30) ~ 1/10000
Day & Night	Removable IR Cut Filter
White Balance	ATW/MANUAL(PRESET)
Min. illumination	Color : 1.4 lx (F1.6 / 50 IRE) High sensitivity Mode : 0.35 lx (F1.6 50 IRE) B/W : 0.05lx (F1.6 50 IRE) High sensitivity Mode : 0.013 lx (F1.6 50 IRE)
WDR	True-WDR
Lens	x 30 Optical Zoom, f=4.3 ~ 129mm, F1.6 ~ F4.7
Network	10/100BASE-T
Video Compression	H.264/ MJPEG
Protocols:	IPv4, ONVIF, TCP/IP, UDP/IP, RTP(UDP), RTSP, NTP, HTTP, DNS, DDNS, DHCP, FTP, SMTP, TCP/IP
Pan/Tilt/Preset Speed)	Preset : 720° /sec, Manual : 1 ~ 360° /sec (Zoom Proportional) , Scan : 1 ~ 360° /sec
Web Browser	Windows 7, Vista, XP, 2000
PTZ Protocol	PelcoP, PelcoD
Optical Zoom	3.5x
Digital Zoom	12x

Resolution	1920x1080 (Full HD), 1280x1024(SXGA), 1280x720 (HD), 1024x768(XGA), 704x480/576(4CIF), 640x480(VGA), 640x360(HVGA), 352x240/288(CIF) , 320x240
Security	Password Protection
Streaming	Yes
SDK(API)	HTTP based API, ONVIF Profile S
VMD, (Video Motion Detection)	User set 4 ROI (Region of Interest), 10 step sensitivity
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player.
Alarm Trigger	VMD External Alarm Input
Alarm Event	Email notification
Power Supply	24VAC / IEEE 802. 3at (POE+)
Edge Storage	SD/SDHC/SDXC Micro SD type (card not included)
Weight	2.8kg
Dimensions	ø220x259(H)mm / ø8.66 x 10.2(H) inch
IP Class	IP66
IK Rating	IK10

